

iC-194DPB



1280x1024 RESOLUTION	5ms RESPONSE TIME	1000:1 CONTRAST RATIO	5:4 ASPECT RATIO	HIGH BRIGHTNESS	ULTRA-WIDE VIEWING ANGLE	BUILT-IN STEREO SPEAKERS	USER-FRIENDLY MENU SCREEN	TILT	VESA WALL-MOUNTABLE	VGA + DVI INPUTS
----------------------	-------------------	-----------------------	------------------	-----------------	--------------------------	--------------------------	---------------------------	------	---------------------	------------------

Technical Specifications

1. Display Size/Type	19" Active Matrix TFT LCD	20. Input Voltage	AC 100~240V, 50/60Hz Autodetect
2. Resolution	1280 x 1024 (SXGA)	21. Power Consumption	42W Maximum
3. Aspect Ratio	5:4	22. Operating Temperature	5°C~35°C / 41°F~95°F
4. Pixel Pitch	0.294(H)mm x 0.294(V)mm	23. Humidity	10%~85%
5. Brightness	300cd/m ²	24. Net Dimensions	16.5"(W) x 16.9"(H) x 7.6"(D)
6. Response Time	5ms (Typical)	25. Net Weight	8.8 lbs.
7. Contrast Ratio	1000:1 (Typical)	26. Gross Dimensions	18.3"(W) x 19.5"(H) x 5.2"(D)
8. Displayable Colors	16.7 Million	27. Gross Weight	11.5 lbs.
9. Viewing Angle (H/V)	170°/160°	28. Certifications	FCC, UL/CUL, CE, C-TICK, VCCI, CB, TUV-Bau Mark, TCO03, GOST, Energy Star, BSMI
10. Color Temperature	9300K, 6500K, 5500K, User Mode	29. Package Contents	iC-194DPB, VGA Cable, Audio Cable, Power Cable, User Manual CD-ROM, Quick Start Guide, Warranty Card
11. Panel Treatment	Anti-Glare Hardcoating	30. UPC Code	842651002619
12. Horizontal Frequency	31kHz - 80kHz	31. Warranty	1-Year Limited
13. Vertical Frequency	55kHz - 75kHz		
14. Video Input(s)	15-Pin D-SUB (VGA), DVI		
15. Speakers	1W x 2 Channel Built-in Stereo		
16. Headphone Out	NA		
17. Tilt	0°~20°		
18. Kensington Slot	Yes		
19. VESA Mounting	100mm x 100mm		

